



安徽艾约塔硅油有限公司

**IOTA CORPORATION LIMITED**

安徽省蚌埠市高新区兴中路 985 号日月  
科技园

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China  
233000

电话: 86-552-3827158

Tel: 86-552-3827158

传真: 86-552-3822922

Fax: 86-552-3822922

## Polyester modified silicone resin IOTA-1038A

### Resin properties and uses:

This product has excellent high temperature performance and water repellent and moisture resistant performance and good electrical insulation properties, arc corona resistance performance. Its weather resistance and chemical stability is also very good. This product has high hardness, high gloss, good fullness, high anti-yellowing performance after fully cured (more than 3H).

### Index:

Appearance:	light yellow to colorless transparent liquid, allows light milk light, no mechanical impurities
Solid content:	59±1%
Film Hardness:	≥ 3H
Viscosity :	350~1000 mPa.s (25°C)
Acid value:	≤ 9mgKOH/g

### Storage:

The product storage period is tentatively scheduled for half a year. This product should be stored in a cool,dry and ventilated place, prevent sun direct radiation; prevent the serious pollution of acid, alkali and should be cut off from the source of the fire and away from the heat source.

### Package:

200/20KGS Iron Bucket.

**Attentions :** This product in the processing process, there will be a large number of xylene and other flammable and explosive, toxic solvents volatile out, should pay

ADD: Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

Tel: 86-552-3827158; Fax: 86-552-3822922 Website: [www.siliconeoil.net](http://www.siliconeoil.net)



TECHNOLOGY MAKES LIFE BETTER

安徽省蚌埠市高新区兴中路 985 号日月  
科技园

电话: 86-552-3827158

传真: 86-552-3822922

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China  
233000

Tel: 86-552-3827158

Fax: 86-552-3822922

attention to strengthen the field of ventilation, pay attention to fire, strictly avoid the fire source. Operator should pay attention to labor protection.

The diluted solvent used for this product shall not contain water, pyridine and impurities containing sulfur compounds, otherwise it will affect the adhesion, dry and other properties of the resin paint film.

This product is used in the process of processing equipment, containers must be clean. To prevent dust and foreign bodies and mixed with water.

Acid, alkali, salt of organic acid and amine compounds have accelerated curing effect on this product, and affects heat resistance and electric properties. Therefore, this product should be kept in strict isolation from these substances.